

Пример конфигурации nginx

Пример конфигурации сайта, который передаёт все запросы бэкенду, кроме картинок и запросов, начинающихся с `"/download/"`.

```
user www www;

worker_processes 2;

pid /var/run/nginx.pid;

# [ debug | info | notice | warn
error_log /var/log/nginx.error_log info;

events {
    worker_connections 2000;

    # use [ kqueue | epoll | /dev/poll | select | poll ];
    use kqueue;
}

http {
    include conf/mime.types;
    default_type application/octet-stream;

    log_format main '$remote_addr - $remote_user [$t
"$request" $status $bytes_sent
"$http_referer" "$http_user_age
"$gzip_ratio"';

    log_format download '$remote_addr - $remote_user [$t
"$request" $status $bytes_sent
"$http_referer" "$http_user_age
"$http_range" "$sent_http_conte

    client_header_timeout 3m;
    client_body_timeout 3m;
    send_timeout 3m;

    client_header_buffer_size 1k;
    large_client_header_buffers 4 4k;

    gzip on;
    gzip_min_length 1100;
    gzip_buffers 4 8k;
    gzip_types text/plain;

    output_buffers 1 32k;
```



NGINX
SPONSORED BY F5

[english](#)

[русский](#)

[новости](#) [en]

[об nginx](#)

[скачать](#)

[безопасность](#) [en]

[документация](#)

[faq](#)

[книги](#) [en]

[сообщество](#)

[компания](#)

[x.com](#)

[blog](#)

[njs](#)

[ingress controller](#)

[gateway fabric](#)

```

postpone_output 1460;

sendfile          on;
tcp_nopush        on;
tcp_nodelay       on;
send_lowat        12000;

keepalive_timeout 75 20;

#lingering_time    30;
#lingering_timeout 10;
#reset_timedout_connection on;

server {
    listen          one.example.com;
    server_name     one.example.com www.one.example.com;

    access_log      /var/log/nginx.access_log main;

    location / {
        proxy_pass      http://127.0.0.1/;
        proxy_redirect   off;

        proxy_set_header Host            $host;
        proxy_set_header X-Real-IP       $remote_addr;
        #proxy_set_header X-Forwarded-For $proxy_add_x_forwarded_for;

        client_max_body_size      10m;
        client_body_buffer_size   128k;

        client_body_temp_path     /var/nginx/client_temp;

        proxy_connect_timeout     70;
        proxy_send_timeout        90;
        proxy_read_timeout        90;
        proxy_send_lowat          12000;

        proxy_buffer_size         4k;
        proxy_buffers              4 32k;
        proxy_busy_buffers_size   64k;
        proxy_temp_file_write_size 64k;

        proxy_temp_path           /var/nginx/proxy_temp;

        charset koi8-r;
    }

    error_page 404 /404.html;

    location = /404.html {
        root /spool/www;
    }

    location /old_stuff/ {
        rewrite ^/old_stuff/(.*)$ /new_stuff/$1 permanent;
    }
}

```

```

location /download/ {

    valid_referers none blocked server_names

    if ($invalid_referer) {
        #rewrite ^/ http://www.example.com/;
        return 403;
    }

    #rewrite_log on;

    # rewrite /download/*/mp3/*.any_ext to /downl
    rewrite ^/(download/.*)/mp3/(.*)\..*$
        /$1/mp3/$2.mp3 brea

    root /spool/www;
    #autoindex on;
    access_log /var/log/nginx-download.access_l
}

location ~* \.(jpg|jpeg|gif)$ {
    root /spool/www;
    access_log off;
    expires 30d;
}
}

```