

Example nginx configuration

An example site configuration that passes all requests to the backend except images and requests starting with "/download/".

```
user www www;

worker_processes 2;

pid /var/run/nginx.pid;

# [ debug | info | notice | warn

error_log /var/log/nginx.error_log info;

events {
    worker_connections 2000;

    # use [ kqueue | epoll | /dev/poll | select | poll ];
    use kqueue;
}

http {

    include conf/mime.types;
    default_type application/octet-stream;

    log_format main '$remote_addr - $remote_user [$t
"$request" $status $bytes_sent
"$http_referer" "$http_user_age
"$gzip_ratio"';

    log_format download '$remote_addr - $remote_user [$t
"$request" $status $bytes_sent
"$http_referer" "$http_user_age
"$http_range" "$sent_http_conte

    client_header_timeout 3m;
    client_body_timeout 3m;
    send_timeout 3m;

    client_header_buffer_size 1k;
    large_client_header_buffers 4 4k;

    gzip on;
    gzip_min_length 1100;
    gzip_buffers 4 8k;
    gzip_types text/plain;

    output_buffers 1 32k;
    postpone_output 1460;
```



NGINX
SPONSORED BY F5

[english](#)

[русский](#)

[news](#)

[about](#)

[download](#)

[security](#)

[documentation](#)

[faq](#)

[books](#)

[community](#)

[enterprise](#)

[community forum \(new\)](#)

[x.com](#)

[blog](#)

[njs](#)

[ingress controller](#)

[gateway fabric](#)

```

sendfile            on;
tcp_nopush          on;
tcp_nodelay         on;
send_lowat          12000;

keepalive_timeout   75 20;

#lingering_time      30;
#lingering_timeout   10;
#reset_timedout_connection on;

server {
    listen            one.example.com;
    server_name        one.example.com www.one.example.com;

    access_log         /var/log/nginx.access_log main;

    location / {
        proxy_pass      http://127.0.0.1/;
        proxy_redirect   off;

        proxy_set_header Host            $host;
        proxy_set_header X-Real-IP       $remote_addr;
        #proxy_set_header X-Forwarded-For $proxy_add_x_forwarded_for;

        client_max_body_size      10m;
        client_body_buffer_size   128k;

        client_body_temp_path      /var/nginx/client_temp;

        proxy_connect_timeout      70;
        proxy_send_timeout         90;
        proxy_read_timeout         90;
        proxy_send_lowat           12000;

        proxy_buffer_size          4k;
        proxy_buffers               4 32k;
        proxy_busy_buffers_size    64k;
        proxy_temp_file_write_size 64k;

        proxy_temp_path            /var/nginx/proxy_temp;

        charset koi8-r;
    }

    error_page 404 /404.html;

    location = /404.html {
        root /spool/www;
    }

    location /old_stuff/ {
        rewrite ^/old_stuff/(.*)$ /new_stuff/$1 permanent;
    }

    location /download/ {

```

```

        valid_referers none blocked server_names

        if ($invalid_referer) {
            #rewrite ^/ http://www.example.com/;
            return 403;
        }

        #rewrite_log on;

        # rewrite /download/*/mp3/*.any_ext to /download
        rewrite ^/(download/.*)/mp3/(.*)\..*$
            /$1/mp3/$2.mp3 break;

        root            /spool/www;
        #autoindex       on;
        access_log       /var/log/nginx-download.access_log;
    }

    location ~* \.(jpg|jpeg|gif)$ {
        root            /spool/www;
        access_log       off;
        expires           30d;
    }
}

```