

org.apache.openjpa.lib.util

Class Localizer.Message

[java.lang.Object](#)

└─ org.apache.openjpa.lib.util.Localizer.Message

Enclosing class:

[Localizer](#)

public static class **Localizer.Message**
extends [Object](#)

A Message can provide a localized message via the [getMessage\(\)](#) method call, and can also provide the original key, package, and substitution array that were used to assemble the message.

Method Summary

String	getKey() The unique key for the localized message.
String	getMessage() The localized message.
String	getPackageName()
Object[]	getSubstitutions() Substitutions inserted into the message.
String	toString()

Methods inherited from class java.lang.[Object](#)

[clone](#), [equals](#), [finalize](#), [getClass](#), [hashCode](#), [notify](#), [notifyAll](#), [wait](#), [wait](#), [wait](#)

Method Detail

getMessage

public [String](#) **getMessage()**

The localized message.

getKey

public [String](#) **getKey()**

The unique key for the localized message.

getSubstitutions

```
public Object[] getSubstitutions()
```

Substitutions inserted into the message.

getPackageName

```
public String getPackageName()
```

toString

```
public String toString()
```

Overrides:

[toString](#) in class [Object](#)

[Overview](#) [Package](#) **[Class](#)** [Use Tree](#) [Deprecated](#) [Index](#) [Help](#)

[PREV CLASS](#) [NEXT CLASS](#)

SUMMARY: [NESTED](#) | [FIELD](#) | [CONSTR](#) | [METHOD](#)

[FRAMES](#) [NO FRAMES](#) [All Classes](#)

DETAIL: [FIELD](#) | [CONSTR](#) | [METHOD](#)

Copyright © 2006-2007 [Apache Software Foundation](#). All Rights Reserved.